

Appl. No. 10/017,513  
Response dated December 7, 2005  
Reply to Office action of December 01, 2005

**In the claims:**

Please amend the claims as follows:

**Claim 1.** (currently amended) An audio monitoring and signal processing apparatus including in combination:

- a) a plurality of audio signal inputs, each operable to receive an audio signal at least two of which receive digital audio signals having different data rates, each of which plurality of audio signals is carried via one or more channels,
- b) a selector for selecting the audio signal which may be present at one of said inputs of a),
- c) a signal processing section responsive to process said selected signal of b) to provided a processed signal carried via one or more channels,
- d) a plurality of output circuits, each responsive to all channels of said processed signal of c) to output said processed signal in a distinct known form,
- e) a monitor circuit responsive to said selected signal of b) and/or said processed signal of c) to provide audible and/or visible monitoring thereof.

**Claim 2.** (currently amended) ~~An apparatus as claimed in claim 1 further including:~~  
An audio monitoring and signal processing apparatus including in combination:

- a) a plurality of audio signal inputs, each operable to receive an audio signal at least two of which receive digital audio signals having different data rates, each of which plurality of audio signals is carried via one or more channels,
- b) a selector for selecting the audio signal which may be present at one of said inputs of a),
- c) a signal processing section responsive to process said selected signal of b) to provided a processed signal carried via one or more channels,
- d) a plurality of output circuits, each responsive to all channels of said processed signal of c) to output said processed signal in a distinct known form,
- e) a monitor circuit responsive to said selected signal of b) and/or said processed signal of c) to provide audible and/or visible monitoring thereof,

Appl. No. 10/017,513

Response dated December 7, 2005

Reply to Office action of December 01, 2005

f) parameters which are established in manufacture and/or by an operator wherein said elements b) and c) operate in response to said parameters such that at least one of the selecting of b) and/or the processing of c) may automatically changes in response to at least one signal present on one said input of a).

**Claim 3.** (original) An apparatus as claimed in claim 1 or 2 further including a mixing element operable to mix a second signal with said selected signal of b) as part of providing said processed signal of c).

**Claim 4.** (currently amended) An audio monitoring and signal conversion method including in combination:

- a) providing a plurality of audio signal input connections, at least one of which is capable of receiving digital audio signals of different data rates,
- b) selecting one of the audio signals which may be present at one of said input connections of a) which selected audio signal is carried via one or more channels,
- c) processing said selected signal of b) to provide a processed signal carried via one or more channels,
- d) outputting all channels of said processed signal of c) in a plurality of distinct known forms,
- e) monitoring said selected signal of b) and/or said processed signal of c) in audible and/or visible form.

**Claim 5.** (currently amended) ~~A method as claimed in claim 4 further including the step of:~~  
An audio monitoring and signal conversion method including in combination:

- a) providing a plurality of audio signal input connections,
- b) selecting one of the audio signals which may be present at one of said input connections of a) which selected audio signal is carried via one or more channels,
- c) processing said selected signal of b) to provide a processed signal carried via one or more channels,

Appl. No. 10/017,513

Response dated December 7, 2005

Reply to Office action of December 01, 2005

d) outputting all channels of said processed signal of c) in a plurality of distinct known forms.

e) monitoring said selected signal of b) and/or said processed signal of c) in audible and/or visible form.

f) utilizing parameters which are established in manufacture and/or by an operator such that at least one of the selecting of step b) and ~~or~~ the processing of step c) ~~may~~ automatically changes in response to at least one signal present on one said input connection of a).

**Claim 6.** (original) A method as claimed in claim 4 or 5 further including a mixing step operable to mix a second signal with said selected signal of b) as part of providing said processed signal of c).

**Claim 7.** (currently amended) An audio monitoring and signal conversion method including in combination:

- a) providing a plurality of audio signal input connections at least one of which is capable of receiving audio signals in digital form having differing data rates,
- b) selecting one of the audio signals which may be present at one of said input connections of a), which audio signal is carried on one or more channels,
- c) processing all of the channels of said selected signal of b) to provide a processed signal which includes one or more channels,
- d) outputting all channels of said processed signal of c) in a plurality of distinct known forms at least one of which is analog and at least one of which is digital,
- e) monitoring said selected signal of b) in audible and/or visible form.

**Claim 8.** (currently amended) An audio monitoring and signal conversion method including in combination:

- a) providing a plurality of audio signal input connections at least one of which is capable of receiving audio signals in digital form having differing data rates,

Appl. No. 10/017,513

Response dated December 7, 2005

Reply to Office action of December 01, 2005

- b) selecting one of the audio signals which may be present at one of said input connections of a), which audio signal includes one or more channels,
- c) processing said selected signal of b) to provide a processed signal which includes one or more channels and which processed signal is responsive to all of the channels of said selected signal,
- d) outputting all channels of said processed signal of c) in a plurality of distinct known forms at least one of which is analog and at least one of which is digital,
- e) monitoring said processed signal of c) in audible and/or visible form.

**Claim 9.** (currently amended) ~~A method as claimed in claim 7 or 8 further including the step of:~~ An audio monitoring and signal conversion method including in combination:

- a) providing a plurality of audio signal input connections,
- b) selecting one of the audio signals which may be present at one of said input connections of a), which audio signal is carried on one or more channels,
- c) processing all of the channels of said selected signal of b) to provide a processed signal which includes one or more channels,
- d) outputting all channels of said processed signal of c) in a plurality of distinct known forms at least one of which is analog and at least one of which is digital,
- e) monitoring said selected signal of b) in audible and/or visible form,
- f) utilizing parameters which are established by an operator such that at least one of the selecting of step b) and the processing of step c) automatically changes in response to at least one signal present on one said input connection of a).

**Claim 10.** (previously amended) A method as claimed in claim 7 or 8 further including a mixing step operable to mix a second signal with said selected signal of b) as part of providing said processed signal of c).

Appl. No. 10/017,513

Response dated December 7, 2005

Reply to Office action of December 01, 2005

**Claim 11.** (currently amended) ~~A method as claimed in claim 7 or 8 wherein in step d) said processed signal is output in analog form and at least two digital forms which are distinct by virtue of having different clock rates.~~ An audio monitoring and signal conversion method including in combination:

- a) providing a plurality of audio signal input connections,
- b) selecting one of the audio signals which may be present at one of said input connections of a), which audio signal is carried on one or more channels,
- c) processing all of the channels of said selected signal of b) to provide a processed signal which includes one or more channels,
- d) outputting all channels of said processed signal of c) in a plurality of distinct known forms at least one of which is analog and at least two of which are digital and are distinct by virtue of having different clock rates,
- e) monitoring said selected signal of b) in audible and/or visible form.

**Claim 12.** (currently amended) ~~A method as claimed in claim 7 or 8 wherein in step d) said processed signal is output in analog form and at least two digital forms which are distinct by virtue of meeting different industry standards for digital audio signals.~~ An audio monitoring and signal conversion method including in combination:

- a) providing a plurality of audio signal input connections,
- b) selecting one of the audio signals which may be present at one of said input connections of a), which audio signal is carried on one or more channels,
- c) processing all of the channels of said selected signal of b) to provide a processed signal which includes one or more channels,
- d) outputting all channels of said processed signal of c) in a plurality of distinct known forms at least one of which is analog and at least two of which are digital and are distinct by virtue of meeting different industry standards for digital audio signals,
- e) monitoring said selected signal of b) in audible and/or visible form.

Appl. No. 10/017,513  
Response dated December 7, 2005  
Reply to Office action of December 01, 2005

Add new claims 13 - 15:

**Claim 13.** (new) An audio monitoring and signal conversion method including in combination:

- a) providing a plurality of audio signal input connections,
- b) selecting one of the audio signals which may be present at one of said input connections of a), which audio signal includes one or more channels,
- c) processing said selected signal of b) to provide a processed signal which includes one or more channels and which processed signal is responsive to all of the channels of said selected signal,
- d) outputting all channels of said processed signal of c) in a plurality of distinct known forms at least one of which is analog and at least two of which are digital and are distinct by virtue of having different clock rates,
- e) monitoring said processed signal of c) in audible and/or visible form.

**Claim 14.** (new) An audio monitoring and signal conversion method including in combination:

- a) providing a plurality of audio signal input connections,
- b) selecting one of the audio signals which may be present at one of said input connections of a), which audio signal includes one or more channels,
- c) processing said selected signal of b) to provide a processed signal which includes one or more channels and which processed signal is responsive to all of the channels of said selected signal,
- d) outputting all channels of said processed signal of c) in a plurality of distinct known forms at least one of which is analog and at least two of which are digital and are distinct by virtue of meeting different industry standards for digital audio signals,
- e) monitoring said processed signal of c) in audible and/or visible form.

Appl. No. 10/017,513  
Response dated December 7, 2005  
Reply to Office action of December 01, 2005

**Claim 15.** (new) An audio monitoring and signal conversion method including in combination:

- a) providing a plurality of audio signal input connections,
- b) selecting one of the audio signals which may be present at one of said input connections of a), which audio signal includes one or more channels,
- c) processing said selected signal of b) to provide a processed signal which includes one or more channels and which processed signal is responsive to all of the channels of said selected signal,
- d) outputting all channels of said processed signal of c) in a plurality of distinct known forms at least one of which is analog and at least one of which is digital,
- e) monitoring said processed signal of c) in audible and/or visible form,
- f) utilizing parameters which are established by an operator such that at least one of the selecting of step b) and the processing of step c) automatically changes in response to at least one signal present on one said input connection of a).

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**